



EDGE HEAVY DUTY
Retractable Fall Arrester

STANDARD : CONFORMING TO EN 360:2002 CE

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Cement Plant	Loading / Unloading
Steel Plant	EOT / Gantry walkway
Refinery	Tanker Inspection
Chemical & Pharma	Maintenance at Vessel

SPECIAL FEATURES



MECHANICAL CHARACTERISTICS

Breaking Strength - 25 kN
Casing - Durable Polyamide
Breaking Force - Less than 6 kN
Fall Arrest Distance - 200mm - 250mm (Maximum)
Temp. Range - -30°C to 50°C

PHYSICAL PARAMETERS

Swivel Snap Hook & EASY 308 Carabiner
Swivel snap hook
Snap hook equipped with fall indicator and swivel action

RETRACTABLE LANYARD

Material - Galvanised steel rope
Diameter - 4 mm
Rope Length - 32 mtr
Breaking Strength - Greater than 25 kN



AVAILABLE LENGTH

25mtr, 32mtr

TEST COMPLIANCE - STATIC STRENGTH

When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is 200mm - 250mm (Max)

Udyogi



FEATURES

Heavy duty wire rope type retractable fall arrester

Included conduit rope

Maximum load capacity 100 kg

STORAGE

Store the block in a dry & normal temperature

MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacturing

Material

Approval & EN standard

Instruction Pictogram

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

1 piece per carton