



Scan Here For More Info



**UD 46 - Safety Spectacle**

STANDARD : EN 166, EN 170, CE, ANSI Z87.1

**INDUSTRY**

Construction & projects  
Cement  
Automotive  
Power & utilities  
Metals & minings

**IDEAL APPLICATIONS**

Material handling  
Dusty area  
Assembly line  
Packaging  
Medical applications

**SPECIAL FEATURES**



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Wrap around single lens design
Nose piece	Polycarbonate	Universal fit, Integral to lens
Side shield	Polycarbonate	Integral with lens
Temple	Polycarbonate	Brow guard spatula type
Sleeve	Nylon	Length position adjustment

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K	40 g.

**FEATURES**

Brow guard temple with polycarbonate lens  
Lens provides side shield protection  
Hard coating on lens  
Lens filters out 99.9% of harmful UV light  
Light weight lens providing full eye-protection against low impact  
Length adjustable temples for all head sizes  
Soft nylon temple tips  
Slim, stylish temple furnish wearer with durability and resilience.  
Suitable for different work environments

**APPLICATION**

Protects eyes exposed to low-level impacts  
Best used for protection against flying small fragments

**STORAGE**

Can be stored in the dark for up to 2years  
Do not store in direct / high heat or sunlight as this may distort the colour  
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

**CLEANING**

Clean it with the soft cloth

**PACKING**

100 pieces per carton

**Udyogi Plastics Private Limited**

294, B. B. Ganguly Street,  
2nd Floor, Kolkata - 700 012

E-mail : [info@udyogi.net](mailto:info@udyogi.net)  
Website : [www.udyogisafety.com](http://www.udyogisafety.com)

Tel. : +91 33 2225 1470/71/72