



Scan Here For More Info



**UD 50 – Safety Spectacle**

STANDARD : ANSI Z87.1, EN 166, CE

**INDUSTRY**

Construction & projects  
Cement  
Automotive  
Power & utilities  
Metals & minings

**IDEAL APPLICATIONS**

Material handling  
Dusty area  
Assembly line  
Packaging  
Medical applications

**SPECIAL FEATURES**



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Wrap around with angle side protection
Frame	Polycarbonate	Brow bar type
Nose piece	Polycarbonate	Integral to lens
Sleeve	Nylon	5 length position adjust
Temple	Nylon	Spatula, extendable
Hinga	Nylon	3 barrel type
Screw	Stainless Steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K	30 g.

**FEATURES**

Brow guard temple with polycarbonate lens  
Lens provides side protection  
Hard coating on lens  
Single piece lens, filters out 99.9% of harmful UV light  
Lens provides perfect impact protection around the eyes  
Length adjustable temple for all head sizes  
Modern temple design & soft nylon temple tips contours to fit head shapes without stress  
Credibly light, resilient & durable protective eyewear for all day wear  
Fashionable design resembles spectacle, suitable for both men and women  
Suitable for different work environment

**APPLICATION**

Protects eyes exposed to low-level impacts  
Best used for protection against flying small fragments

**STORAGE**

Can be stored in the dark for up to 2years  
Do not store in direct / high heat or sunlight as this may distort the colour  
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

**CLEANING**

Clean it with the soft cloth

**PACKING**

100 pieces per cartoon

**Udyogi Plastics Private Limited**

294, B. B. Ganguly Street,  
2nd Floor, Kolkata - 700 012

E-mail : [info@udyogi.net](mailto:info@udyogi.net)  
Website : [www.udyogisafety.com](http://www.udyogisafety.com)

Tel. : +91 33 2225 1470/71/72