



Scan Here For More Info



UD 90 – Safety Spectacle

STANDARD : IS 5983

INDUSTRY

Construction & projects
Cement
Automotive
Power & utilities
Metals & minings

IDEAL APPLICATIONS

Material handling
Dusty area
Assembly line
Packaging
Medical applications

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Full wrap with side protection
Nose bridge	Nylon 6	Bridge is a part of the frame
Nose pad	TPR	Bridge is a part of the frame
Sleeve	Nylon 6	4 length position adjust
Temple	Nylon 6	Adjustable
Hinge / screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	26 g.

FEATURES

Brow guard temple with polycarbonate lens
Lens provides side protection
Hard coating on lens
Lens filters out 99.9% of harmful UV light
Lens provides perfect impact protection around the eyes
Length adjustable temple for all head sizes
Modern temple design & soft nylon temple tips contours to fit head shapes without stress
Credibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION

Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

Clean it with the soft cloth

PACKING

100 pieces per cartoon

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72