




**4810 GI**  
Eye/Face wash wall mounted

STANDARD : IS 10592:2018  Meets ANSI Z358.1

INDUSTRY	IDEAL APPLICATIONS
Food/Steel	Corrosive Environment.
Chemical/Mining	Battery charging areas.
Pharma	Spraying operations.
Laboratories	Against Acid / Chemical Spillage.
Automobile	Dipping operations.
-	Hazardous substances dispensing areas

**SPECIAL FEATURES**

 POWDER COATED/ ANTI CORROSIVE	 HIGH DELUGE ACTION	 EASY MAINTENANCE	 EASY OPERATION	 FIRST AID AIDING EQUIPMENT
--	---	---	---	---

**EYE / FACE WASH WALL MOUNTED**

Eye wash fountain head shall be within 830-1140 mm (83 cm-114 cm) above floor surface as per standard

**EYE WASH HEAD**

Two high-flow sprays, operated at low pressure, which washes the eye and face.

Anti-dust cover protects the head from airborne contaminants and automatically opens with water pressure.

Distance between two eye wash head shall be 140 to 200 mm

**PUSH TO OPEN VALVE**

½" BSP Ball valve connects units to uninterrupted water supply as per requirements

**FEATURES**

Water inlet connections of 1/2" NB for eye / face wash.

Water outlet connection - 1¼" NB

Eye wash discharge rate - 12 lpm. (minimum)

Manually operated valve for hazel free usage

Receptor bowl attached for minimize wastage of water

With foot pedal for hands free operation to supply and control water flow through eye wash heads

GI Wall bracket for mounting the shower on the walls



**SUPPLY WATER CONDITION**

**MATERIAL**

Supply Water	Drinking / Tepid Water	Pipe	GI with powder coated
Operating Pressure	2.1 Kg / cm <sup>2</sup> (30 PSI)	Fitting	GI with powder coated
Operating Temp	Ambient	-	-

**EYE WASH BOWL**

Highly visible Yellow ABS bowl resistant to damage from most acid, alkali and oil

Size of ABS Bowl 270 ± 3 mm

**PACKING**

**GROSS WEIGHT**

1 set per box

3.600 kg

**Udyogi**