

**EDGE PLUS - Safety Spectacle** 

STANDARD: ANSI Z87.1, EN 166, CE



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

## SPECIAL FEATURES | IGHT WEIGHT | SP.95 UV PROTECTION | HARD COATING | LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	10 base curve, full eye protection
Nose piece	PVC	Universal, snap-in
Temple	Polycarbonate	Spatula with co-injection soft pad
Temple tip	TPE	Integral to temple (co-injection)
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	К	30 g.

FEATURES
Polycarbonate temple with polycarbonate lens
Lens provides perfect impact protection around the eye
Hard coating on lens
Lens filters out 99.9% of harmful UV light
Close-fitting unitary front with dual 10 base curvature offers wide and unobstructed vision
Snug-fitting nose pieces conform to fit all kinds of nasal profiles
Soft TPE temple tips
Incredibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APP	LICAT	ION

Protects eyes exposed to low-level impacts

Best used for protection against flying small fragments

## **STORAGE**

Can be stored in the dark for up to 2 years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to  $+30^{\circ}$  C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton

## Udyogi

294, B. B. Ganguly Street,2nd Floor, Kolkata - 700 012

E-mail: info@udyogi.net

Website: www.udyogisafety.com

Tel.: +91 33 2225 1470/71/72