






WS01 (2D)

Webbing Sling with both side D Ring

STANDARD : CONFORMING TO EN 795-CLASS-B

| INDUSTRY | IDEAL APPLICATIONS | SPECIAL FEATURES | | |
|--|------------------------------|--|--|---|
| Construction | Working at Height |  FALL ARREST |  STRONG |  TEMPORARY ANCHORAGE |
| Telecommunication | Creating Temporary Anchorage | | | |
| Road & Bridge Concs | | | | |
| Transmission | Fall Arrest | | | |
| FEATURES | | AVAILABLE LENGTH | | |
| Anchor slings made of polyester webbing with D-ring at both end | | 1, 1.5, 2 meter | | |
| D-ring made of high strength Alloy Steel | | PHYSICAL PARAMETERS | | |
| Strength : 23 kN | | Stitching Threads - High tenacity virgin multifilament polyester | | |
| Standard : Conforms to EN 795 Class-B | | Metal Components - High Quality Alloy Steel, Zinc Plated, Free From Any Sharp Edges | | |
| MECHANICAL CHARACTERISTICS | | STORAGE | | |
| WEBBING Material - Polyester | | Store Webbing sling in a dry area away from ultra violet rays | | |
| WEBBING Width - 44 +/- 1 mm | | Do not store in direct / high heat or sunlight as this may distort the colour | | |
| WEBBING Breaking Strength - 23 kN | | Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold | | |
| TEST COMPLIANCE - DYNAMIC STRENGTH | | MARKINGS | | |
| When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 m | | Manufacturers Logo, details & mailing address | | |
| TEST COMPLIANCE - STATIC STRENGTH | | Model No., Batch No., Serial No. | | |
| Withstands a load of 23 kN for 3 minutes each attachment element | | Year of Manufacturing | | |
| CLEANING | PACKING | Material | | |
| Use clean piece of cloth to wipe the dust | 1 piece per polybag | Approvals & EN | | |
| | | Instruction Pictogram | | |

