





RL22
Safety Lanyard

STANDARD: CONFORMING TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Construction	Work at Height
Metals & Mining	Ladder Climbing
	Fall Arrest
Transmission	Rescue

SPECIAL FEATURES	ROPE MATERIAL	WEIGHT
 LIGHT WEIGHT  FALL RESTRAINT	12 mm Polyester Rope	1.90kg



BREAKING STRENGTH	LANYARD LENGTH	STITCHING THREAD
23kN (Min)	2 meter (Hook to hook)	High Tenacity Virgin Multifilament Polyester

TEST COMPLIANCE - STATIC STRENGTH
With a force of 15 kN, the fully developed energy absorber shall withstand the static strength test without tearing or rupture.

TEST COMPLIANCE - DYNAMIC PERFORMANCE
The test shall be conducted with a rigid steel mass of 100 kgs, raising the mass to its maximum height and without using an additional chain lanyard. The fall arrest force F max shall not exceed 6 kN, the arrest distance H shall not exceed 5.75 meter.

MECHANICAL CHARACTERISTICS
Minimum Static strength of lanyard 22 kN
Maximum dynamic load – 6 kN
Maximum Fall arrest distance – 5.75 meter
Maximum capacity 100 kg (For the use of single user only)
Maximum Carabiner 308 gate opening – 18 mm
Maximum SH-60 hook gate opening – 55 mm

FEATURES
Energy Absorbing Double Polyester Rope Lanyard with available length of 1.5 meter, 1.8 meter, 2 meter
On absorber side connected with EASY 308 carabiner and on other side connected with two EASY SH 60 Scaffolding Hooks

Udyogi



MARKINGS		STORAGE	
Manufacturers Logo		Store the harness in a dry area away from ultraviolet rays.	
Model No., Batch No., Serial No.		Do not store in direct / high heat or sunlight as this may distort the Colour.	
Year of Manufacture		Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.	
Material		CLEANING	PACKING
Approvals & CE		Use clean piece of cloth to wipe the dust	10 pieces per carton
Instruction Pictogram			