



Scan Here For More Info

TECHNICAL DATA SHEET

SN003 Plus - SAFETY NET FOR FALL PROTECTION

Safety Net:

Safety Net is a Secondary Fall arrest measure to ensure workers safety and efficiency by providing a collective level of protection.

Features:

- Durable and resistant to harsh environments
- High-strength materials for maximum load capacity
- Customizable sizes and shapes to fit specific applications
- Easy installation and maintenance
- Manufactured with ISI Marked Rope & as per IS 11057:1984

Applications:













Weight: (Size: 10 x 5mtr)

17 KGS Approx

Safety Net (Triple Layer)

Specifications:

Border Rope: 12 mm PP Rope (ISI Marked) Breaking Strength 2210kgf. 1st Layer 4mm PP Rope , having mesh size 100mm x 100mm. Breaking Strength 214 Kg 2nd Layer 0.75mm Overlay HDP Net, having mesh size 20-25mm 3 rd Layer 120 GSM Monofilament Net. Monofilament UV Stabilized Net with Welding / Grinding Splatter Resistant. Fabrication Type: Hand Knotted Tie Rope & Tie Cord: 12 mm dia PP rope of 2 meters length at for 4 corner of border rope only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Standard/ Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS : 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply. Marking/Lable Manufacturer Name/Logo, Model No. , Batch No. , Size		
Breaking Strength 214 Kg 2nd Layer 0.75mm Overlay HDP Net, having mesh size 20-25mm 120 GSM Monofilament Net. Monofilament UV Stabilized Net with Welding / Grinding Splatter Resistant. Fabrication Type: Hand Knotted 12 mm dia PP rope of 2 meters length at for 4 corner of border rope only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Standard/ Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS: 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	Border Rope:	12 mm PP Rope (ISI Marked) Breaking Strength 2210kgf.
2nd Layer 0.75mm Overlay HDP Net, having mesh size 20-25mm 120 GSM Monofilament Net. Monofilament UV Stabilized Net with Welding / Grinding Splatter Resistant. Fabrication Type: Hand Knotted 12 mm dia PP rope of 2 meters length at for 4 corner of border rope only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Standard/ Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS: 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	1st Layer	4mm PP Rope , having mesh size 100mm x 100mm.
120 GSM Monofilament Net. Monofilament UV Stabilized Net with Welding / Grinding Splatter Resistant. Fabrication Type: Hand Knotted Tie Rope & Tie Cord: 12 mm dia PP rope of 2 meters length at for 4 corner of border rope only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Standard/ Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS: 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	Breaking Strength	214 Kg
Welding / Grinding Splatter Resistant. Fabrication Type: Hand Knotted 12 mm dia PP rope of 2 meters length at for 4 corner of border rope only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Standard Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS: 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	2nd Layer	0.75mm Overlay HDP Net, having mesh size 20-25mm
Tie Rope & Tie Cord: 12 mm dia PP rope of 2 meters length at for 4 corner of border rope only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Rope Certified to IS 5175: 1992, & Safety Net as per IS: 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	3 rd Layer	
only. & Tie cord of 2mtr at every 1.5 meter interval. Standard Size: As per your requirement (Minimum Length & Width Should be 3 Mtr) Standard/ Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS : 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	Fabrication Type:	Hand Knotted
Standard/ Approved: Rope Certified to IS 5175: 1992, & Safety Net as per IS : 11057:1984 Certification Manufacturer Test Certificate provided at the time of supply.	Tie Rope & Tie Cord:	
Certification Manufacturer Test Certificate provided at the time of supply.	Standard Size:	As per your requirement (Minimum Length & Width Should be 3 Mtr)
The state of the s	Standard/ Approved:	Rope Certified to IS 5175: 1992, & Safety Net as per IS: 11057:1984
Marking/Lable Manufacturer Name/Logo, Model No. , Batch No. , Size	Certification	Manufacturer Test Certificate provided at the time of supply.
	Marking/Lable	Manufacturer Name/Logo, Model No. , Batch No. , Size

Udyogi

294, B. B. Ganguly Street, 2nd Floor, Kolkata - 700 012 E-mail: info@udyogi.net

Website: www.udyogisafety.com

Tel.: +91 33 2225 1470/71/72