



### SUSPENSION TRAUMA STRAP

INDUSTRY	IDEAL APPLICATIONS	
Work at a height		
Wind	Suspend at a height, after	
Power	arrest a fall.	
Construction		





# MECHANICAL CHARACTERISTICS Material: Durable polyester Webbing: 20mm wide Closures: Zipper fasteners Hook: Alloy steel with golden zinc plating Capacity: 141kg) Weight: 0.2 lbs. (91g) Length: Adjustable 1.1 m/1.0 m/0.9 m/0.8m/0.7m Length: Adjustable 1.1 m/1.0 m/0.9 m/0.8m/0.7m

## Length: Adjustable 1.1 m/1.0 m/0.9 m/0.8m/0.7m CLEANING Use clean piece of cloth to wipe the dust

PACKING	
10 pieces per carton	

#### **FEATURES**

The two packs are compact, lightweight and easily installed to most harness sizes, styles and brands.

After a fall, the packs can quickly be unzipped, deploying the web loop and hook straps which can easily be connected and adjusted to provide a strap for the foot to conveniently step into.

Length of the strap is adjustable at five size, can be adjust according to user comfort

This allows the worker to stand in their harness and relieve the pressure through the body while waiting for rescue.

Safety Strap Helps Prevent Suspension Trauma

#### **STORAGE**

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

#### Udyogi

E-mail: info@udyogi.net Website: www.udyogisafety.com Tel.: +91 33 2225 1470/71/72