



## TRIPOD EDGE-210

Anchor

**STANDARD: CONFORMING TO EN795:2012**

INDUSTRY	IDEAL APPLICATIONS
Municipal Corporation	Anchorage  Confined space entry
Oil & Gas	
Pharmaceutical	

### SPECIAL FEATURES



### MECHANICAL CHARACTERISTICS

High strength aluminium alloy

Strength: 22 kN

Safe working load limit: 100 kg

### FEATURES

With two mounted pulleys at the head of the Tripod in the extension of the main leg for passing a cable

Having two auxiliary eye bolts as attachment points

Aluminum alloy cast head, legs in aluminum

Steel support-shoes provided with rubber sole to increase friction and impart more stability

Strength of anchorage point greater than 10 kN

Every Tripod is provided with inbuilt fixture for attaching our winch

Every Tripod is provided with Kit Bag

Net Weight : 17.13kgs(approx.)

### STORAGE

Can be stored and transported in their original kit bag/ cartons to avoid wear & tear due to atmospheric moisture, excessive heat or cold.



### PHYSICAL PARAMETERS

Maximum working height : 2100 mm

Adjustable Height : From 1400 mm to 2100 mm

Wheelbase : 1000 mm to 1500 mm

Maximum load capacity : 100 Kg

### MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

### PACKING

1 pc per carton