



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Construction	-
Metal	-
Heavy Engineering	-
Production Process	-
Chemical Industry	-

## TANGO IMPACT Rx - Safety Shoe Safety shoe - PVC Sole

STANDARD: IS: 15298: PART-3

## **SPECIAL FEATURES**











COMPONENT	MATERIAL	ADVANTAGE	
Upper	Rexin	Excelent resistance to hydrolysis, abrasion, scratch etc.	
Lining	Synthetic with foam padded	Keeps the foot warm & dry and balance the moisture inside the shoe	
Toe Cap	Alloy Steel	Protective reinforcement in the toe which protects the foot from falling objects	
Sole	PVC	Resistance to slip, chemicals, acid, alkali & heat resistance of 150°C for 1 minute	
Insocks	EVA	Improve shock absorption, provides pain relief, ankle & leg injuries	

COLLAR	TONGUE	Eyelet	Lace	Thread	WEIGHT
Foam padded	d Foam padded	Round Aluminium	Flat-Nylon dual colour	Nylon 3/6 ply	1255 gms (Size-8) with tolerance of ± 5% for all sizes

FEATURES		
Very good physical & chemical, acid, alkali properties		
High tear & tensile strength		
Excellent resistance to abrasion		
Excellent breathability		
Ageing resistance		
Durability		
Ease of care		
Light weight		
Water repellant		
Anti-bacterial & no odours		
Steel Toe cap		

APPLICATION
Warehouse
Construction
Service Industry, Manufacturing Industries

STORAGE	
Store in a dark, dry & well ventilated area	
Keep away from sources of heat	
Keep shoe of the floor	

CLEANING	PACKING
With a mixture of warm water & mild liquid soap and wipe them down with a damp cloth to remove dirt & dust	20 pairs per carton

## **Udyogi Plastics Private Limited**

294, B. B. Ganguly Street,2nd Floor, Kolkata - 700 012

E-mail: info@udyogi.net

Website: www.udyogisafety.com

Tel.: +91 33 2225 1470/71/72