




#### **TECHNICAL DATA SHEET**



#### **Product Introduction:**

- These unique features make Udyogi safety earmuffs made of ABS, it is equipped with specialized clips or brackets that slot into designated attachment points on the industrial helmet. suitable for a wide range of demanding industrial applications, providing both protection and comfort.
- Designed to meet EN352-3:2020 standard,
   it ensures maximum protection for the wearer in various high noise environments.



#### Features:

- These helmet mountable earmuffs quickly and easily attach to universal slots of hard hats.
- Can be used with a combination of face shield.
- Made of high impact, heat resistant, moisture & cold proof ABS (Acrylonitrile Butadiene Styrene).
- The earmuffs reduce pressure on the ear drum.
- Soft padding on ABS cups provides a comfortable seal around the ears, reducing pressure and enhancing comfort for long-term use.
- No exposure of metal parts & good workmanship having no sharp edges which may cause injuries to the ear and other parts of the body.
- Polyurethane foam, sponge filled air pad, soft & hygienic muff inside for maximum attenuation of unpleasant air borne noise.

#### **Benefits:**

- **Safety Compliance:** EY66-6 earmuffs provide reliable and consistent noise reduction, ensuring compliance with safety regulations. This can prevent potential fines or penalties related to non-compliance.
- Easy to Clean EY66-6 surfaces are smooth and non-porous, making them easy to wipe clean and maintain.
- **Recyclable:** ABS is a thermoplastic, meaning it can be melted down and reformed multiple times without significantly degrading its properties. This makes it inherently recyclable
- **Durability:** This earmuffs can withstand harsh industrial environments and last longer than those made. from less durable materials

Udyogi

E-mail: info@udyogi.net Website: www.udyogisafety.com Tel.: +91 33 2225 1470/71/72





# **Product Specifications:**

M odel EY66-6

**Product Type:** Helmet mounted ear muff **Cup Material:** Dual mould and slim ABS cup

Inserts: PU (Polyurethane foam)
Cushions: Foam with PVC black lid
Metal Spring: SS (Stainless Steel)

Clip material: Co-polymer

Weight: 290 grams.

Testing Frequency Ranges (Hz): 125, 1000, 8000

Attenuation Results (dB): 34(High); 27(Medium); 21(Low)

Attenuation Rating: SNR: 30 dB NRR: 25 dB

Color: Black/Neon

**Packaging:** 20 pair per box **Standard:** EN352-3:2020

# Construction



**Insert:** Inner Foam Paded cushion

## **Applications:**

- Protects hearing by reducing exposure to high decibel levels in noisy environments.
- EY66-6 is widely used across various fields to provide essential hearing protection, enhance safety, and improve comfort and productivity.
- These are crucial in any setting where exposure to high noise levels is a concern, ensuring workers' hearing health and compliance with safety regulations
- Used to protect from dust and water.

#### **Industry**:

These helmets are utilized for their protective and practical features in various industries such as



Steel



Construction



Cement Industry



Railroad Industry



Forestry & Logging



Automobile



Chemical



Oil & Gas



Minin



Power



**Aviation** 



Pharmaceutical



General Manufacturing



Food Processing

E-mail: info@udyogi.net Website: www.udyogisafety.com Tel.: +91 33 2225 1470/71/72





# **Safety Information:**

- This product contains metallic components that may increase electricity hazard.
- This must be regularly inspected for cracked parts and replaced as needed. Life for foam cushion is approx 6 months.

### **Usage Instructions:**

- Insert Udyogi Ear Muff jack into the helmet's adapter slots until they snap into place with a click sound.
- Bring the Ear Muff cups down to ear position by turning it into circular motion.
- Make sure the Ear Muff cups and the cup holding bands are not in contact with the outer lining
  or the edge of the hard hat when in the 'usage' position, otherwise it may leak.
- Push the Ear Muff jack for dismantling

# Storage:

- Stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
- May be stored in the dark for up to 1 year
- Do not store in direct / high heat or sunlight as this may distort the shell.

Udyogi

E-mail: info@udyogi.net Website: www.udyogisafety.com Tel.: +91 33 2225 1470/71/72