



Scan Here For More Info



6PA3 - Face Shield

STANDARD: EN 166, ANSI Z87.1

INDUSTRY	IDEAL APPLICATIONS	
Pharmaceutical	ARC welding	
Chemical	Heavy, medium, light gas welding	
Cement	Atomic hydrogen welding	
	Heavy, medium, light cutting	
Construction Automotive		
	Torch brazing	
	Spot welding, soldering	

SPECIAL FEATURES











COMPONENT	MATERIAL	HEAD BAND	ADVANTAGE
Visor	PVC	Elasticated rubber	Covers the entire facial region

LENS	FILTER	COLOUR	LENS SIZE	WEIGHT
Glass	DIN (customized), Clear (customized)	Dark Green, Clear	(4 ^{1/2} X 3 ^{1/2}) inch (114 mm X 89 mm)	290 g

FEATURES
Flip type front window with clear and DIN glass, extend fully to cover a wearer's face
Elasticated head band designed fit with universal helmet
Provides full protection against splashes, spatters etc.
Lens filter DIN glasses, protects IR rays emitted from welding related techniques
Protects against 99.9% UV protection
Protections against high-speed impact
Fits over the spec
Best optical quality (Astigmatic refractive power, prismatic refractive power, and light diffusion)
Suitable for different work environment

APPLICATION

Can be used where eye & face exposed to welding, Cuttingetc.

Protects face exposed to splashes, high speed flying small & medium fragments

STORAGE

Can be stored in the dark for up to 1 year

Do not store direct / high heat or sunlight as this may distort $% \left(1\right) =\left(1\right) \left(1\right) \left($

Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

CLEANING	PACKING
Clean cloth can be used	Cartoon

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,2nd Floor, Kolkata - 700 012

E-mail: info@udyogi.net

Website: www.udyogisafety.com

Tel.: +91 33 2225 1470/71/72