



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Pharmaceutical	ARC welding
Chemical	Heavy, medium, light gas welding
Cement	Atomic hydrogen welding
Construction	Heavy, medium, light cutting
Automotive	Torch brazing
	Spot welding, soldering

6PAU - Face Shield

STANDARD : EN 166, ANSI Z87.1

SPECIAL FEATURES				
LIGHT WEIGHT	99.9% UV PROTECTION	HARD COATING	CHEMICAL SPLASH PROTECTION	MEDIUM IMPACT RESISTANT

COMPONENT	MATERIAL	CLIP ATTACHMENT	ADVANTAGE
Visor	PVC	Non-universal (UDYOGI ultra helmet)	Covers the entire facial region

LENS	FILTER	COLOUR	LENS SIZE	WEIGHT
Glass	DIN (customized), Clear (customized)	Dark Green, Clear	(4 1/2" X 3 1/2) inch (114 mm X 89 mm)	290 g

FEATURES
Flip type front window with clear and DIN glass, extend fully to cover a wearer's face
Designed to worn with Udyogi 'Ultra' helmet
Provides full protection against splashes, spatters etc.
Lens filter DIN glasses, protects IR rays emitted from welding related techniques
Protects against 99.9% UV protection
Protections against high-speed impact
Fits over the spec
Best optical quality (Astigmatic refractive power, prismatic refractive power, and light diffusion)
Suitable for different work environment

APPLICATION
Can be used where eye & face exposed to welding, cutting etc.
Protects face exposed to splashes, high speed flying small & medium fragments

STORAGE
Can be stored in the dark for up to 1 year
Do not store direct / high heat or sunlight as this may distort
Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

CLEANING	PACKING
Clean cloth can be used	Cartoon

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72