



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Pharmaceutical	Light and medium gas welding
Chemical	Cutting
Cement	Torch brazing
Construction	Spot welding, soldering
Automotive	Welding observation

**FC 48G - Face Shield**

STANDARD : EN 166, ANSI Z87.1

SPECIAL FEATURES				
LIGHT WEIGHT	99.9% UV PROTECTION	HARD COATING	CHEMICAL SPLASH PROTECTION	MEDIUM IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Visor	Polycarbonate	Covers the entire facial region

COMPONENT	COLOUR	FILTER	SIZE	THICKNESS	IMPACT RESISTANCE
Visor	Dark green	DIN 5	(8 X 15 1/2) inch (203 mm X 394 mm)	1 mm	B (120 m/s)

FEATURES
Polycarbonate masks that extend fully to cover a wearer's face
Edges fitted with aluminium beading for easy adjustment to face contour
Lens filter DIN 5, protects from IR rays emitted from welding related techniques
Protects against 99.9% UV protection
Provides wide vision
Protections against high-speed impact
Protects against splashes, spatters
Protective films on both sides ( Prevent damages and scratches during transportation )
Fits over the spec
Best optical quality ( Highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion )
Suitable for different work environment

APPLICATION
Protects face exposed to splashes, high speed flying small & medium fragments
Also can be used where eye & face exposed to gas welding, cutting, soldering, welding observation etc.

STORAGE
Can be stored in the dark for up to 1 year
Do not store direct / high heat or sunlight as this may distort
Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

CLEANING	WEIGHT	PACKING
Clean cloth can be used	120 g	Cartoon

**Udyogi Plastics Private Limited**

294, B. B. Ganguly Street,  
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net  
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72