



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS	
Mining	Mining	
	Mud handling	
	Foggy area	

SPECIAL FEATURES	
LICHTWEIGHT	LOWIMPACT

STANDARD: EN 166

G MESH - Safety Spectacle

COMPONENT	MATERIAL	ADVANTAGE
Lens	Stainless steel	One piece wire mesh 4.5 base curve
Frame	Nylon	-
Side shields	Polycarbonate	Slide on
Nose piece	Nylon	Universal, integral to frame
Temple	Nylon	Spatula
Hinge	Nylon	3 Barrel Type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	WEIGHT
Black wire net	40 g.

FEATURES		
Brow guard nylon frame with wire mesh lens		
Side shield provides additional side protection		
Lens protects from the any environment where there is danger of eye injury from small or medium size particles		
Lens protects from fogging, the area where fogging is a major problem		
Full front lens provides perfect impact protection around the eyes		
Does not provide protection against fine dust or splash		
Soft temple tips contours to ensure comfort fit		
Incredibly light, resilient & durable protective eyewear for all day wear		
Suitable for different work environment		

APPLICATION

Protects eyes exposed to low level impact, Best used for protection against any environment where there is danger of eye injury from small or medium size particles and where fogging is a major problem

STORAGE

Can be stored in the dark for up to 2 years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to $+30^{\circ}$ C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per cartoon

Tel.: +91 33 2225 1470/71/72

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,2nd Floor, Kolkata - 700 012

E-mail: info@udyogi.net

Website: www.udyogisafety.com