Product Data Sheet

Arc Shield for Hoods Model IM22-AFA-25V

Arc flash protection face shield with Velcro[®] pattern for hoods. ATPV 25 calories. Available for purchase only through Paulson's OEM customers. Contact Paulson for OEM contact information.



Product Details	
Product Name	IM22-AFA-25V
Material	Polycarbonate
Color	Green
Product Weight	0.74 lbs.
Specification	Meets NFPA 70E; Meets/Tested ASTM F2178; ANSI Z87+S
Description	Single lens arc window. Injection molded to shape. Velcro® riveted design securing three layers together (Velcro®, window, and gasket). For use with hoods. Rated 25 cal/cm ² .
Competitive Advantage	This product maximizes the ATPV (Arc Thermal Protection Value) of 25 cal/cm ² . Excellent field of view. Premium anti-fog and anti-abrasion coated for a longer service life. Structurally sound while giving the product a self supporting frame.
Applications	This arc window is used in association with dielectric head protection and accessories to provide protection from the hazards of arc flash. Arc flash is a defined hazard by NFPA-70E.
Comments	See the videos on Paulson's arc flash products at: <u>http://www.paulsonmfg.com/videos.p</u> <u>hp</u> Do not use this arc window for electric
	arc welding exposures.







Paulson Manufacturing Corp. 46752 Rainbow Canyon Road, Temecula, CA 92592 Phone: 951-676-2451 | Toll Free: 800-542-2451 | Fax: 951-676-3481 info@paulsonmfg.com | www.paulsonmfg.com