



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

TWISTER – Safety Spectacle

STANDARD : ANSI Z87.1, EN 166, CE

SPECIAL FEATURES				
LIGHT WEIGHT	99.9% UV PROTECTION	ANTI-FOG COATING	HARD COATING	LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	9.5 base
Frame	Polycarbonate	Lens snapped in the frame
Nose piece	TPE	Universal fit
Temple	Polycarbonate	Width adjustable
Width adjustment	Nylon	Rotable
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K & N	30 g.

FEATURES
Brow guard temple with polycarbonate lens
Lens provides wraparound fitting- perfect impact protection around the eyes
Anti-fog & hard coating on lens
Lens filters out 99.9% of harmful UV light
Unique & length adjustable temple for customize fitting
Modern temple design, soft TPE nose piece, soft temple tips contours to fit all head shapes without stress
Retainer on the sides of the temple for retaining the ear plug
Credibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION
Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE
Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72