



Scan Here For More Info



EDGE-DD AK MF - Safety Shoe
Microfiber safety shoe

STANDARD: IS: 15298-Part 2

INDUSTRY	IDEAL APPLICATIONS
Heavy Engineering	-
Construction	-
Metal	-
Oil & Gas	-
Production Process	-

SPECIAL FEATURES













COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber plain	Excelent resistance to hydrolysis, solvent, abrasion etc.
Lining	Spacer with foam padded-200 gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy steel	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Polyurethane - Double density	Resistance to slip and bending performance, shock absorber, chemicals
Insocks	PU Foam	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	D-Ring	Round-Nylon dual colour	Nylon 3/6 ply	1096 gms for size-8 with tolerance of ± 5% for all sizes

FEATURES
Very good physical & chemical properties
High tear & tensile strength
Excellent resistance to abrasion
Excellent breathability
Ageing resistance
Durability
Ease of care
Light weight
Water repellant
Anti-bacterial & no odours
Alloy Steel Toe cap - 200 J

APPLICATION
Transport : Automotive/Aerospace
IT & Technology - Telecom, Production Process
Oil & Gas, Construction

STORAGE
Store in a dark, dry & well ventilated area
Keep away from sources of heat
Keep shoe of the floor

CLEANING	SIZE	PACKING
With a mixture of warm water & mild liquid soap and wipe them down with a damp cloth to remove dirt & dust	5 to 12	10 pairs per carton

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,2nd Floor, Kolkata - 700 012

E-mail: info@udyogi.net

Website: www.udyogisafety.com

Tel.: +91 33 2225 1470/71/72