



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Heavy Engineering	-
Logistics & Transport	-
Metal	-
Manufacturing Process	-
Construction	-
	-

## TANGO DD MF - Safety Shoe Microfiber safety shoe

STANDARD: IS: 15298 🔄

## **SPECIAL FEATURES**













COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber barton print	Excelent resistance to hydrolysis, solvent, abrasion, scratch etc.
Lining	Synthetic with foam padded-200 gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy Steel	Protective reinforcement in the toe which protects the foot from falling objects
Sole	PU - Double density	Resistance to slip and bending performance, shock absorber, chemicals
Insocks	EVR/Rubber	Improve shock absorption, provides pain relief, ankle & leg injuries

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Brass	Round-Nylon single colour	Nylon 3/6 ply	983 gms for size-8 with tolerance of $\pm$ 5% for all sizes

FEATURES
High tear & tensile strength
Excellent breathability
Excellent resistance to abrasion
Good physical & chemical properties
Ageing resistance
Durability
Ease of care
Light weight
Water repellant
Anti-bacterial & no odours
Steel Toe cap

APPLICATION
Transport : Automotive/Aerospace
IT & Technology - Telecom, Energy Industry - Production process
Building & Construction, Pharma, Hotel Industry

STORAGE
Store in a dark, dry & well ventilated area
Keep away from sources of heat
Keep shoe of the floor

CLEANING	SIZE	PACKING
With a mixture of warm water & mild liquid soap and wipe them down with a damp cloth to remove dirt & dust	5 to 12	20 pairs per carton

## **Udyogi Plastics Private Limited**

294, B. B. Ganguly Street, 2nd Floor, Kolkata - 700 012 E-mail: info@udyogi.net

Website: www.udyogisafety.com

Tel.: +91 33 2225 1470/71/72