



Scan Here For More Info



**UD 71 - Safety Spectacle**

STANDARD : IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

SPECIAL FEATURES				
LIGHT WEIGHT	99.9% UV PROTECTION	ANTI-FOG COATING	HARD COATING	LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	9.75 base curve, wrap around design w/side protection
Nose piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula
Hinge	Polycarbonate	5 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K & N	20 g.

FEATURES
Polycarbonate temple with polycarbonate lens
Snug-fitting wraparound lens provides perfect impact protection around the eyes
Anti-fog & hard coating on lens
Lens filters out 99.9% of harmful UV light
Close-fitting unitary front with dual 9.75 base curvature offers wide and unobstructed vision
Soft temple tips
Incredibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION
Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE
Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton

**Udyogi**