UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

# WL20
## Safety Lanyard

**STANDARD : CERTIFIED TO EN 354:2010, EN 355:2002** CE

| INDUSTRY | IDEAL APPLICATIONS |
|---|---|
| - | Work at Height |
| - | Fall Arrest |

### SPECIAL FEATURES

LIGHT WEIGHT | FALL RESTRAINT

### ROPE MATERIAL

44m (+/- 1mm) wide Polyester Webbing

### STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

### FEATURES

Energy Absorbing Single Polyester Webbing Lanyard

One side (Lanyard End) connected with SH-60 scaffolding hook and on other side connected with

| BREAKING STRENGTH | LANYARD LENGTH |
|---|---|
| 23kN (Min) | 1.8 mm (Hook to Hook) |

### MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approval & IS marking
- Instruction Pictogram

### CLEANING

Use clean piece of cloth to wipe the dust

### STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct / high heat or sunlight as this may distort the Colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

### PACKING

10 pieces per carton

**Udyogi**

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

**Tel. :** +91 33 2225 1470/71/72