





BL12
Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
-	Work At Height
-	Fall Arrest



SPECIAL FEATURES	
 LIGHT WEIGHT	 FALL RESTRAINT

ROPE MATERIAL
10.5mm Kernmantle Rope

STITCHING THREAD
High Tenacity Virgin Multifilament Polyester

FEATURES
Energy Absorbing Single Braided Rope Lanyard
One side (Lanyard End) connected with EASY 308 Carabiner and on other side Loop attachment

BREAKING STRENGTH	LANYARD LENGTH
23kN (Min)	1.8 mm (Hook to Hook)

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approvals & CE
Instruction Pictogram

CLEANING
Use clean piece of cloth to wipe the dust

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

PACKING
10 pieces per carton

Udyogi