UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

RL22
Safety Lanyard

STANDARD : CERTIFIED TO EN 354:2010, EN 355:2002 CE

INDUSTRY	IDEAL APPLICATIONS
Construction	Work at Height
Metals & Mining	Ladder Climbing
Transmission	Fall Arrest
	Rescue

SPECIAL FEATURES

LIGHT WEIGHT | FALL RESTRAINT

ROPE MATERIAL
12mm Polyamide Rope

STITCHING THREAD
High Tenacity Virgin Multifilament Polyester

FEATURES
Energy Absorbing Double Polyamide Rope Lanyard

On absorber side connected with EASY 308 Carabiner and on other side connected with two EASY SH 60 Scaffolding Hooks

BREAKING STRENGTH	LANYARD LENGTH
23kN (Min)	1.8 mm (Hook to Hook)

MARKINGS
- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approvals & CE
- Instruction Pictogram

CLEANING
Use clean piece of cloth to wipe the dust

STORAGE
- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct / high heat or sunlight as this may distort the Colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

PACKING
10 pieces per carton

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72