





TWL22
Safety Lanyard

STANDARD : CERTIFIED TO ANSI Z359.13-2013, EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
-	Work At Height
-	Fall Arrest
-	Rescue

SPECIAL FEATURES	
 LIGHT WEIGHT	 FALL RESTRAINT

ROPE MATERIAL
44m (+/- 1mm) wide Polyester Webbing

FEATURES
Energy Absorbing Double Webbing Lanyard with tie-back D-rings
Forged Steel snap hooks at both the ends
Hooks & Carabiners made of Alloy steel, conforming to EN362
Light Weight & High Strength Lanyard

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
10 pieces per carton



STITCHING THREAD
High Tenacity Virgin Multifilament Polyester

BREAKING STRENGTH	LANYARD LENGTH
23kN (Min)	1.8 mm (Hook to Hook)

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approvals & CE
Instruction Pictogram

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

Udyogi