UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

WEBBING SLING WS1D
Sling with one side D Ring

STANDARD : CONFORMING TO EN 795-CLASS-B

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Telecommunication	Creating Temporary Anchorage
Road & Bridge Conts	Fall Arrest
Transmission	

SPECIAL FEATURES

FALL ARREST | STRONG | TEMPORARY ANCHORAGE

MECHANICAL CHARACTERISTICS

- WEBBING Material - Polyester
- WEBBING Width - 44 +/- 1 mm
- WEBBING Breaking Strength - 23 kN

PHYSICAL PARAMETERS

- Stitching Threads - High tenacity virgin multifilament polyester
- Colour - Blue & Green
- Metal Components - High Quality Alloy Steel, Zinc Plated, Free From Any Sharp Edges

TEST COMPLIANCE - DYNAMIC STRENGTH

When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 m

AVAILABLE LENGTH

1, 1.5, 2 meter

TEST COMPLIANCE - STATIC STRENGTH

Withstands a load of 23 kN for 3 minutes each attachment element

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72

UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

FEATURES
Tie of Anchor slings made of polyester Round Sling with D-ring at one end
Loops at other end
Strength: 23 kN
For 1 user
Standard: Conforms to EN 795 Class-B

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Approvals & EN
Instruction Pictogram

STORAGE
Store Webbing sling in a dry area away from ultra violet rays
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
1 pieces per carton

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72