



## EDGE HEAVY DUTY

### Retractable Fall Arrester

STANDARD : CONFORMING TO EN 360:2002 CE

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Cement Plant	Loading / Unloading
Steel Plant	EOT / Gantry walkway
Refinery	Tanker Inspection
Chemical & Pharma	Maintenance at Vessel

SPECIAL FEATURES		
 LIGHT WEIGHT	 H-SHAPED	 EASY TO USE
 STRONG	 WATER RESISTANT	

MECHANICAL CHARACTERISTICS
Breaking Strength - 25 kN
Casing - Durable Polyamide
Breaking Force - Less than 6 kN
Fall Arrest Distance - 200mm - 250mm (Maximum)
Temp. Range - -30°C to 50°C

PHYSICAL PARAMETERS
Swivel Snap Hook & EASY 308 Carabiner
Swivel snap hook
Snap hook equipped with fall indicator and swivel action

RETRACTABLE LANYARD
Material - Galvanised steel rope
Diameter - 4 mm
Rope Length - 30 mtr
Breaking Strength - Greater than 25 kN

TEST COMPLIANCE - STATIC STRENGTH
When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is 200mm - 250mm (Max)



AVAILABLE LENGTH
25meter, 30meter

FEATURES
Heavy duty wire rope type retractable fall arrester
Included conduit rope
Maximum load capacity 100 kg

STORAGE
Store the retractable in a dry area away from ultraviolet rays.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Approval & EN standard
Instruction Pictogram

PACKING
1 piece per carton

CLEANING
Use clean piece of cloth to wipe the dust