





## HAND DESCENDER

STANDARD : CONFORMING TO EN341 - CLASS A

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES	
Facade Cleaning	Rescue	 FALL ARREST	
Painting & Maintenance	Rope Access	<b>PHYSICAL PARAMETERS</b> Light weight Aluminium body  Single Action Lever to use the device  Cast. design to attach carabiner to the descender	
	Descending		
MECHANICAL CHARACTERISTICS			
Material - Cast aluminium			
Weight - 340 gm			
Finish - Coloured, Anodized			
Use with 10.5mm Kernmantle Rope			
TEST COMPLIANCE - DYNAMIC STRENGTH		MARKINGS	
When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 m		Manufacturers Logo	
		Model No., Batch No., Serial No.	
		Year of Manufacturing	
		Material	
		Approvals & EN	
		Instruction Pictogram	
FEATURES		STORAGE	
Single Use Lever to descend makes it easy to control		Store the retractable in a dry area away from ultraviolet rays	
Equipped with a unique dual self-braking system which initiates the brake as soon as the handle is released or clasped too tightly			
Multipurpose use device - Can be used for self descend or assisted rescue		Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.	
Shape of device is designed to easily grip within the palm of the user			
CLEANING	PACKING		
Use clean piece of cloth to wipe the dust	1 piece per polybag		