



EL22 Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Metals & Mining	Work At Height
Pharmaceuticals	Ladder Climbing
Chemicals	Fall Arrest
	Rescue

SPECIAL FEATURES



LIGHT WEIGHT



FALL RESTRAINT

ROPE MATERIAL

35m (+/- 1mm) wide Elasticated Polyester Webbing

FEATURES

Energy Absorbing Double Elasticated Webbing Lanyard for fall arrest

One side carabiner and other side two tower hooks, made of Aluminum Alloy, conforming to EN362

Elasticated webbing extends as per user requirement, Relaxed Length 1.4m, Extended Length 1.8m

Light Weight & High Strength Lanyard

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

10 pieces per carton



STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

BREAKING STRENGTH

23kN (Min)

LANYARD LENGTH

1.8 meter (Hook to Hook)

MARKINGS

Manufacturers Logo

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.