





EL61
Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Wind	Work At Height
Pharmaceuticals	Ladder Climbing
	Fall Arrest
Chemicals	Rescue



SPECIAL FEATURES	
 LIGHT WEIGHT	 FALL RESTRAINT

ROPE MATERIAL
35m (+/- 1mm) wide Elasticated Polyester Webbing

STITCHING THREAD
High Tenacity Virgin Multifilament Polyester

FEATURES
Energy Absorbing Double Elasticated Webbing Lanyard
One side (Lanyard End) connected with SH-61 aluminium hook and on other side connected with auto locking quarter turn aluminium Carabiner

BREAKING STRENGTH	LANYARD LENGTH
23kN (Min)	1.8 meter (Hook to Hook)

CLEANING
Use clean piece of cloth to wipe the dust

MARKINGS
Manufacturers Logo
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approvals & CE
Instruction Pictogram

PACKING
10 pieces per carton

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

Udyogi