



EDGE-EX MF (PU-NR)
Microfiber Safety Shoe

STANDARD : IS : 15298-Part 2

INDUSTRY	
Heavy Engineering	Chemicals, Oil & Gas
Steel	Mining

SPECIAL FEATURES					
TOE CAP	ANTI-SKID	ANTI-BACTERIAL	HEAT-RESISTANT OUTSOLE	ODOUR LESS	WATER RESISTANCE



COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber plain	Excellent resistance to hydrolysis, abrasion etc.
Lining	Spacer with foam padded-200 gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy steel	Protective reinforcement in the toe which protects the foot from falling object
Sole	PU - Nitrile rubber	Resistance to slip and bending performance, shock absorber, chemicals, acids, alkalies, heat resistance upto 300° cel. for 01 minute
Insocks	PU foam	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Round brass	Round Nylon	Nylon 3/6 ply	1145 gms for size-8 with tolerance of ± 5% for all sizes

FEATURES
Very good physical & chemical properties
High tear & tensile endurance
Excellent resistance to abrasion
Excellent breathability
Ageing resistance
Durability
Ease of care
Extra light weight
Water repellent
Anti-bacterial & Odor free
Alloy steel toe cap - 200 J

APPLICATION
Transport : Automotive / Aerospace
IT & Technology - Telecom, Production Process
Oil & Gas, Construction

STORAGE
Store away from sunlight, at room temperature
Keep in a dry, well ventilated space
Keep in cleaned and ready to be used condition

PACKING	SIZE	CLEANING
10 pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Udyogi