



Scan Here For More Info



FC 38 - Face Shield

STANDARD : EN 166, ANSI Z87.1

INDUSTRY

Pharmaceutical
Chemical
Cement
Construction
Automotive

IDEAL APPLICATIONS

Chemical handling
Labs
Grinding
Paint shop
Poisonous material handling

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



CHEMICAL SPLASH PROTECTION



MEDIUM IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Visor	Polycarbonate	Covers the entire facial region

COMPONENT	COLOUR	SIZE	THICKNESS	IMPACT RESISTANCE
Visor	Clear	(9 X 14 1/2) inch (228 mm X 368 mm)	2 mm	B (120 m/s)

FEATURES

Polycarbonate, transparent masks that extend fully to cover a wearer's face

Provides wide vision

Protects against 99.9% UV protection

Protections against high-speed impact

Protects against splashes, spatters

Protective films on both sides (Prevent damages and scratches during transportation)

Fits over the spec

Best optical quality (Highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion)

Suitable for different work environment

APPLICATION

Protects face exposed to splashes, high speed flying small & medium fragments

Also protects face against irritating mist and potentially infectious materials

STORAGE

Can be stored in the dark for up to 1 year

Do not store direct / high heat or sunlight as this may distort

Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

CLEANING

Clean cloth can be used

PACKING

100 pcs per carton

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72