




H 5101
Safety Gloves

STANDARD :  EN 388 : 2016
4544D

INDUSTRY	IDEAL APPLICATIONS
Petrochemical	General handling
Automotive	Heavy Material Handling
Glass	General Manual Jobs
Metal structure construction	Assembly, Machining / Stamping / Cutting
Machinery & equipment's	Raw material handling

SPECIAL FEATURES				
 OILY ENVIRONMENT	 GRIP	 ABRASION	 CUT-RESISTANT	 DEXTERITY

LINER TYPE	COATING
UHMWPE liner	Flat nitrile & sandy nitrile

ADVANTAGE
Cut and liquid resistance with high dexterity

FEATURES
UHMWPE (ultra high molecular weight polyethylene) cut level 5 / D liner
3/4 th flat nitrile & palm sandy nitrile
Coating will give high level of liquid / semi-liquid permeation protection and liner will provide cut level 5 / D protection
Seamless knitted liner for ultimate comfort and higher flexibility



LINER COLOUR	COATING COLOUR
Salt pepper	Blue / Black

COATING TYPE	SIZE
3/4 th flat nitrile & palm sandy nitrile	8 & 9

CUFF STYLE	CERTIFICATION
Normal overlocked	EN388 : 2016 - 4544D

APPLICATION
Assembly line, assembling metal parts and components
Handling sharp or irregular metal pieces
Press shop, scrap handling, hardware assembly etc

STORAGE
Store in cool and dry place
Do not store in direct / high heat or sunlight
Can be stored and transported in their original cartons

LAUNDERABLE	PACKING
Yes (as per instruction)	120 pairs per carton

Udyogi