



## PL02

### Work Positioning Lanyard

STANDARD : CONFORMING TO EN 358:2018 **CE**

INDUSTRY	IDEAL APPLICATIONS
Wind	Rescue
	Rope Access
Telecom	Ladder Climbing
Transmission	Work Positioning
	Fall Arrest

#### SPECIAL FEATURES



LIGHT WEIGHT



FALL RESTRAINT

#### ROPE MATERIAL

10.5mm Kernmantle Rope

#### FEATURES

One Side carabiner with alloy steel grip adjuster and other side stitched eye / knot

New compact grip adjuster, used for hands free working

Rope ends with PE tube for durability of stitching

Adjustable gradually and moves freely

With Abrasion protection sleeve to prevent rope from any damage

#### CLEANING

Use clean piece of cloth to wipe the dust

PACKING	WEIGHT
10 pieces per carton	1175g



#### STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

#### BREAKING STRENGTH

25kN (Min)

#### LANYARD LENGTH

2.0 meter

#### MARKINGS

Manufacturers Logo

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approval & IS marking

Instruction Pictogram

#### STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.