






WPL 01

Work Positioning Lanyard

STANDARD : CONFORMING TO EN 358 **CE**

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES
Wind	Work Positioning Lanyard	 LIGHT WEIGHT  FALL RESTRAINT
Telecom		
Power		
Construction		 WORK POSITIONING



MECHANICAL CHARACTERISTICS
Webbing Material - Polyester
Webbing width - 44 mm
Webbing Breaking Strength - 22 kN (Min)
The breaking tenacity of the synthetic fiber of webbing shall be at least - 0.6 N/ tex
Temp. Range - -30°C to 50°C

HOOK DETAILS
Material - Steel karabiner with screw gate and adjuster buckles
Hook opening - 18mm
Breaking Strength - Greater than 25 kN (karabiner)

MARKINGS
Manufacturers Logo
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approval & IS marking
Instruction Pictogram

TEST COMPLIANCE - STATIC STRENGTH
Apply a 5 kN static force for 3 minutes, record the slippage shall not exceed 50 mm and apply another 15 kN static force for 3 minutes, the work positioning lanyard shall not be fracture

TEST COMPLIANCE - DYNAMIC STRENGTH
The work positioning lanyard shall not allow the dummy to be release, when fitted to a 100 kg rigid mass and released from 1 m height.

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

FEATURES
Two EASY308 carabiner and adjustable buckles
Abrasion protection sleeves
Extremely light weight and compact lanyard
Extended Length - 2meter

CLEANING	PACKING
Use Clean piece of cloth to wipe the dust	10 pieces per carton

Udyogi