






EDGE NANO TWIN
Retractable Block

STANDARD : EN360:2002

| INDUSTRY | IDEAL APPLICATIONS | SPECIAL FEATURES | | |
|--------------------|-----------------------------------|---|---|--|
| Construction | Working at Height |  FALL ARREST |  STRONG |  LIGHT WEIGHT |
| Process plants | Ladder Climbing | | | |
| Grinding Unit | Loading/Unloading point | | | |
| Manufacturing Unit | Bag House and vessels maintenance | | | |

| MECHANICAL CHARACTERISTICS | FEATURES |
|---|--|
| Webbing Material : UHMWPE Material (Ultra high molecular weight Poly Ethylene). | Has a Swivel Snap hook at one end and Swivel top to connect. |
| Min. Breaking Strength : 20kN | Extremely Compact, durable and light weight. |
| Average force less than : 1.350 lbs | High capacity external shock absorber with impact indicator. |
| Fall Arrest Distance : 42 inch (Max.) | Quick-action braking system. |
| Fall Arrest Force : 1.800 lbs (Max.) | High strength anti corrosion components. |
| Safe Working Load : 140kg | Combination of dual unit, with connector. |
| Free fall distance : 2' (Max.) | Make of durable & light weight webbing material. |
| Length : 1.8 m | |
| Weight : 1.250 kgs | |



| MARKINGS |
|---|
| Manufacturers Logo, details & mailing address |
| Model No., Batch No., Serial No. |
| Year of Manufacturing |
| Material |
| Instruction Pictogram |

| STORAGE |
|---|
| Store the retractable in a dry area away from ultraviolet rays |
| Can be stored and transported in their original carton to avoid corrosion due to atmospheric moisture, excessive heat or cold |

| CLEANING |
|---|
| Use clean piece of cloth to wipe the dust |

| PACKING |
|-----------------|
| 1 piece per box |

Udyogi