



Scan Here For More Info



ET 20 – Ear Muff

STANDARD : EN352-1

INDUSTRY

Cement

Steel

Automotive

Mining

Chemical

IDEAL APPLICATIONS

Metal processing

Shop floor

Wood working

Drilling

Construction & projects

SPECIAL FEATURES



LIGHT WEIGHT



ACTIVE NOISE REDUCTION



HEARING OPTIMIZATION



EAR PROTECTION

PRODUCT TYPE	HEARING PROTECTION STYLE	ATTENUATION RATING (NRR)	COLOUR	WEIGHT
Earmuff	Head mounted	23 decibel	Yellow	180 g.

COMPONENT	MATERIAL	ADVANTAGE
Cups	Styrene-butadiene copolymer and Styrene homo-polymer	Large to hold extra materials for use in extreme noise
Inserts	PU (Polyurethane foam)	Provides comfort to the ear
Cushions	PVC (Polyvinyl chloride), polypropylene glycol, calcium carbonate	Used to reduce noise
Cushion cover	PVC	Covered the cushion protect from any damage
Headband	Polycarbonate	Universal fit, can be used over the head

FEATURES

Head mounted earmuff

Made of high impact, heat resistant, moisture & cold proof polypropylene

Headband is adjustable for any standard head size

Adjustable ear-cups with 360 degree rotating headband

Soft foam - filled cushions and large ear cup openings to provide greater protection and comfort.

Polypropylene foam sponge filled air pad, soft & hygienic muff inside for maximum attenuation of unpleasant air borne noise.

No exposure of metal parts & good workmanship having no sharp edges which may cause injuries to the ear and other parts of body

Light weight & conversant for all day use

Can be used with combination of ear plug

APPLICATION

Can be used to reduce extreme noise

Protects from hearing loss

Also protects dust

STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)

May be stored in the dark for up to 1 year

Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING

Clean using soft cloth, do not use water

PACKING

50 pieces per carton

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72