



Scan Here For More Info



**FUSION 6000 Series**  
- Safety Helmet

STANDARD : EN 397, CE

**INDUSTRY**

Cement  
Automotive  
Power & utilities  
Metals & mining  
Iron & steel

**IDEAL APPLICATIONS**

Construction & projects works  
Material handling  
Shop floor  
Packaging  
Maintenance

**SPECIAL FEATURES**



LIGHT WEIGHT



RECYCLABLE



STRONG & DURABLE



TEMPERATURE RESISTANT



RATCHET FIT

**COLOURS:**



COMPONENT	MATERIAL	ADVANTAGES
Shell	ABS (Acrylonitrile Butadiene Styrene)	Resistant to high radiant heat
Peak	ABS	20 mm, peak protects eye & face from falling objects
Brim	ABS	Rim around the shell, drains rain water
Cradle	LDPE / Textile	8-point adjustment, perfect load distribution
Head band	LDPE	Universal fit, dia. 52 cm – 66 cm
Sweat band	Brushed cloth on foam	Sweat absorbent, long time use
Chin strap	PP	Holds the shell, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Ratchet	Nylon	Fully adjustable, smooth & universal fit
Slot	Universal slots on the both side	Compatible with head & face PPE accessories
Ventilation	Both side of the crown ventilated	3 point ventilation on each side for air circulation

**FEATURES**

Shell made of ABS compound

8-point plastic / textile suspension with slip fit or ratchet fit adjustment

Unique crown ventilation system provides air circulation & comfort

High quality sweat band provides comfort

Tensile strength is higher than HDPE helmets yet light weight

Lower extension of nape strap to prevent dislodging

Excellent rain management system to effectively reduce the flow of water down the neck

Aesthetic, aerodynamic look with smooth finish – solid colour resin for a permanent, no-chip, no-peel finish

Designed for use in industries where there is a hazard, which can damage skull

Available in non-vented fusion (Electrical resistance up to 2 kVA electrical power)

**APPLICATION**

Protects head from falling objects

Protects splashes, spatters etc.

**STORAGE**

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)

Shell may be stored in the dark for up to 5 years

Do not store in direct / high heat or sunlight as this may distort the shell

**CLEANING**

Clean using warm soapy water and soft cloth

Do not use solvents or abrasives

**WEIGHT**

Slip fit - 352 grams,  
Ratchet fit - 357 grams

**PACKING**

50 pieces per carton

**Udyogi**

294, B. B. Ganguly Street,  
2nd Floor, Kolkata - 700 012

E-mail : [info@udyogi.net](mailto:info@udyogi.net)  
Website : [www.udyogisafety.com](http://www.udyogisafety.com)

Tel. : +91 33 2225 1470/71/72