



Scan Here For More Info



**LightOn V - Safety Helmet**

STANDARD : EN 397, CE, ANSI Z89.1, Type 1, Class - C

INDUSTRY	IDEAL APPLICATIONS
Cement	Construction & projects works
Automotive	Material handling
Power & utilities	Shop floor
Metals & mining	Packaging
Iron & steel	Maintenance

**SPECIAL FEATURES**

LIGHT WEIGHT	RECYCLABLE	STRONG & DURABLE	TEMPERATURE RESISTANT	RATCHET FIT
--------------	------------	------------------	-----------------------	-------------

COLOURS: White

COMPONENT	MATERIAL	ADVANTAGES
Shell	ABS (Acrylonitrile Butadiene Styrene)	Resistant to high radiant heat
Peak	ABS	20 mm, peak protects eye & face from falling objects
Brim	ABS	Rim around the shell, drains rain water
Cradle	Textile	8-point adjustment, perfect load distribution
Head band	Plastic	Universal fit, dia. 52 cm – 63 cm
Sweat band	Soft pad	Non-contact sweat band maximizes comfort, long time use
Chin strap	PP	Holds the shell, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Ratchet	Nylon	Fully adjustable, smooth & universal fit
Slot	Universal slots on the both side	Compatible with head & face PPE accessories
Ventilation	Both side of the crown ventilated	4 point ventilation on each side for air circulation

FEATURES
Shell made of ABS compound
8-point textile suspension with ratchet fit adjustment
Unique crown ventilation system provides air circulation & comfort
High quality sweat band provides comfort
Tensile strength is higher than HDPE helmets yet light weight
Lower extension of nape strap to prevent dislodging
Excellent rain management system to effectively reduce the flow of water down the neck
Aesthetic, aerodynamic look with smooth finish – solid colour resin for a permanent, no-chip, no-peel finish
Designed for use in industries where there is a hazard, which can damage skull, face

APPLICATION
Best use for climbing, height work, confined space entry, facade cleaning, construction, general manufacturing, heavy infrastructure, industrial maintenance etc.
Can be used where ambient temperature is high

STORAGE
Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
Shell may be stored in the dark for up to 5 years
Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING	WEIGHT	PACKING
Clean using warm soapy water and soft cloth	546 grams	20 pieces per carton
Do not use solvents or abrasives		

**Udyogi**

294, B. B. Ganguly Street,  
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net  
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72