





UB102
Full Body Harness

STANDARD: CONFORMING TO EN 361:2002, IS 3521(Part 1): 2021  

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Maintenance	Ladder Climbing
-	Fall Arrest

SPECIAL FEATURES



FALL ARREST



CLIMBING



RESTRAINT



CLASS-A



CLASS-L

WEBBING MATERIAL

Polyester

WEBBING WIDTH

44 +/- 1 mm

WEBBING BREAKING STRENGTH

23 kN

STITCH THREADS MATERIAL

High tenacity virgin multifilament polyester

STITCH THREADS COLOUR

White

METAL COMPONENTS

High quality alloy steel, zinc plated, free from any sharp edges.

HARNES COLOUR

Yellow & Black

WEIGHT

1 kg (approx.) Without lanyard

TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 KN applied for 3 min.

TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 m.



Udyogi



FEATURES	MARKINGS
One dorsal D-ring for fall arrest.	Manufacturers Logo, details & mailing address
Two textile chest attachment loop for fall arrest.	Model No.
Easy to put on and off during emergency.	Batch No. & Serial No.
Ideally positioned sit-strap for extended comfort.	Year of Manufacture
Built-in dual colour webbing for easy orientation.	Material
Fall Indicator: A fall indicator system with tag provided to ensure easy notice when a fall occurred & subsequent discarding of the PPE. Fall indicator tag located below the back plate to the back side of both the shoulder straps.	Approval & IS marking
	Instruction Pictogram
CLEANING	STORAGE
Use Clean piece of cloth to wipe the dust.	Store the harness in a dry area away from ultraviolet rays.
	Do not store in direct/ high heat or sunlight as this may distort the colour.
PACKING	Can be stored and transported in their original carton to avoid corrosion due to atmospheric moisture, excessive heat or cold.
10 pieces per carton.	