



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Iron & steel	Construction & projects works
Cement	Material handling
Automotive	Shop floor
Power & utilities	Packaging
Metals & mining	Maintenance

UI 1211 - Safety Helmet

STANDARD : IS 2925:1984, DGMS Approved

SPECIAL FEATURES



COLOURS:



COMPONENT	MATERIAL	ADVANTAGES
Shell	HDPE (High density poly ethylene)	Resistant to high level impact
Peak	HDPE	48 mm, peak protects eye & face from falling objects
Brim	HDPE	Rim around the shell, drains rain water
Cradle	Plastic	6-point adjustment, perfect load distribution
Head band	Plastic	Universal fit, dia. 53 cm – 61 cm
Sweat band	Brushed cloth on foam	Sweat absorbent, long time use
Chin strap	PP	Holds the shell, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Nape strap	Plastic	Fully adjustable, smooth & universal slip fit

FEATURES

Shell made of HDPE compound
Dome shape to provide complete coverage
Smooth finish – solid colour resin for a permanent, no-chip, no-peel finish
Greater impact resistance and crack resistance
6-point plastic suspension with slip fit adjustment
Adjustable chin strap for customized fit and comfort
High quality sweat band provides comfort
Radiant heat resistivity higher than ABS helmets yet light weight
Designed for use in industries where there is a hazard, which can damage skull

APPLICATION

Protects head from falling objects
Protects splashes, spatters etc.

STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
Shell may be stored in the dark for up to 5 years
Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING	WEIGHT	PACKING
Clean using warm soapy water and soft cloth	Slip fit - 320 grams	50 pieces per carton
Do not use solvents or abrasives		

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72