



Scan Here For More Info





Ultra Pro 3000 Series – Safety Helmet

STANDARD : 🔄 IS 2925:1984, EN 397, CE

INDUSTRY	IDEAL APPLICATIONS	
Iron & steel	Construction & projects works	
Cement	p. 6 je 6 to 11 to 11 to	
	Material handling	
Automotive		
	Shop floor	
Power & utilities		
	Packaging	
Metals & mining	Maintenance	

SPECIAL FEATURES



COMPONENT	MATERIAL	ADVANTAGES	
Shell	HDPE (High density poly ethylene)	Resistant to high level impact	
Peak	HDPE	39 mm, peak protects eye & face from falling objects	
Brim	HDPE	Rim around the shell, drains rain water	
Cradle	HDPE/TEXTILE	4-point adjustment, perfect load distribution	
Head band	HDPE	Universal fit, dia. 54 cm - 62 cm	
Sweat band	Brushed cloth on foam	Sweat absorbent, long time use	
Chin strap	PP	Holds the shell, universal fit	
Chin strap clip	Nylon	Attachment between shell and chin strap	
Nape Strap	HDPE	Slip fit/Ratchet fit for all head sizes	
Slot	Universal slots on the both sides	Slots compatible with head & face PPE accessories	

FEATURES

Shell made of HDPE compound

Aesthetic look with smooth finish – solid colour resin for a permanent, no-chip, no-peel finish

Three ribs at the top of the helmet & better head clearance

Greater shock absorption & impact resistance

4-point plastic suspension with plastic slip fit, Textile slip/ratchet fit

Adjustable chin strap for customized fit and comfort

High quality sweat band for comfort

Radiant heat resistivity higher than ABS helmets yet light weight

Designed for use in industries where there is a hazard, which can damage skull

APPLICATION

Protects head from falling objects

Protects splashes, spatters etc.

STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)

Shell may be stored in the dark for up to 5 years Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING	WEIGHT	PACKING
Clean using warm soapy water and soft cloth	365 grams	50 pieces per carton
Do not use solvents or abrasives		

Udyogi