







## ULTRA EDGE

### Safety Spectacle

STANDARD :  IS 5983, EN 166, CE, ANSI Z87.1

INDUSTRY	IDEAL APPLICATIONS
Cement	Material handling
Automotive	Dusty area
Power & utilities	Assembly line
Metals & minings	Packaging
Construction & projects	Medical applications



SPECIAL FEATURES			
 LIGHT WEIGHT	 99.9% UV PROTECTION	 HARD COATING	 LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGES
Lens	Polycarbonate	Full wraparound for enhanced protection
Nose Piece	Polycarbonate	Universal fit, integral to lens
Temple	Polycarbonate	Spatula type

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K	27.50 g.

FEATURES
Polycarbonate lens with polycarbonate temple
Close-fitting unitary front with dual base curvature offers wide and unobstructed vision
Hard coating on lens
Lens filters out 99.9% of harmful UV light
Snug-fitting wraparound lens provides perfect impact protection around the eyes
Modern temple design tips contours to fit head shapes without stress
Integral vented, stylish temple design
Incredibly light, resilient & durable protective eyewear for all day wear
Non-metallic design for di-electric use
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION
Protects eyes exposed to low-level impacts
Best used for protection against flying small particles

STORAGE
Can be stored in the dark and sealed condition for up to 2 years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Just air dry after the rinsing or dipping in water	100 pieces per carton
Do not wipe off the water	

### Udyogi