





STANDARD: EN 166, CE, ANSI Z87.1

INDUSTRY	IDEAL APPLICATIONS	
Cement	Material handling	
Automotive	Dusty area	
Power & utilities	Assembly line	
Metals & minings	Packaging	
Construction & projects	Medical applications	



SPECIAL FEATURES











E-mail: info@udyogi.net

Website: www.udyogisafety.com

COMPONENT	MATERIAL	ADVANTAGES
Lens	Polycarbonate	Wide & wraparound
Nose Piece	Polycarbonate	Universal fit, integral to lens
Temple	Polycarbonate	Sleek spatula type, flexible with side protection

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K & N	37 g.

FEATURES

Over the spectacle design-fit over most prescription glasses

Polycarbonate lens with polycarbonate temple

Integral ventilated side protection

Non-metalic design for di-electric use

Anti-fog & hard coating on lens

Lens filters out 99.9% of harmful UV light

Lens provides perfect impact protection around the eyes

Modern sleek temple design contours to fit all head shapes without stress

Incredibly light, resilient & durable protective eyewear for all day wear

Fashionable design resembles spectacle, suitable for both men and women

Suitable for different work environment

APPLICATION

Over the spectacle

Protects eyes exposed to low-level impacts

Best used for protection against flying small particles

STORAGE

Can be stored in the dark and sealed condition for up to 2 years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0 $^{\circ}$ C to +30 $^{\circ}$ C)

CLEANING	PACKING	
Just air dry after the rinsing or dipping in water	100 pieces	
Do not wipe off the water	per carton	

Tel.: +91 33 2225 1470/71/72

Udyogi