



Scan Here For More Info

ULTRA-Z Safety Spectacle

STANDARD :  IS 5983, EN 166, CE, ANSI Z87.1

INDUSTRY		IDEAL APPLICATIONS	
Construction & projects		Material handling	
Cement		Dusty area	
Automotive		Assembly line	
Power & utilities		Packaging	
Metals & minings		Medical applications	

SPECIAL FEATURES				
				
LIGHT WEIGHT	99.9% UV PROTECTION	HARD COATING	LOW IMPACT RESISTANT	

COMPONENT	MATERIAL	ADVANTAGES		
Lens	Polycarbonate	Full wrap with side protection		
Nose Piece	Polycarbonate	Universal fit, integral to lens		
Temple	Polycarbonate	Spatula type		

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K	25 g.

FEATURES	APPLICATION
Polycarbonate lens with polycarbonate temple	Protects eyes exposed to low-level impacts
Close-fitting unitary front with dual base curvature offers wide and unobstructed vision	Best used for protection against flying small particles
Hard coating on lens	
Lens filters out 99.9% of harmful UV light	
Snug-fitting wraparound lens provides perfect impact protection around the eyes	
Modern temple design tips contours to fit head shapes without stress	
Incredibly light, resilient & durable protective eyewear for all day wear	
Non-metallic design for di-electric use	
Fashionable design resembles spectacle, suitable for both men and women	
Suitable for different work environment	

STORAGE
Can be stored in the dark and sealed condition for up to 2 years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton

Udyogi