



ULTRA-Z
Safety Spectacle

STANDARD : EN 166, CE, ANSI Z87.1

INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications



SPECIAL FEATURES				
LIGHT WEIGHT	99.9% UV PROTECTION	ANTI-FOG COATING	HARD COATING	LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGES
Lens	Polycarbonate	Full wrap with side protection
Nose Piece	Polycarbonate	Universal fit, integral to lens
Temple	Polycarbonate	Spatula type

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K & N	25 g.

FEATURES
Polycarbonate lens with polycarbonate temple
Close-fitting unitary front with dual base curvature offers wide and unobstructed vision
Anti-fog & hard coating on lens
Lens filters out 99.9% of harmful UV light
Snug-fitting wraparound lens provides perfect impact protection around the eyes
Modern temple design tips contours to fit head shapes without stress
Incredibly light, resilient & durable protective eyewear for all day wear
Non-metallic design for di-electric use
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION
Protects eyes exposed to low-level impacts
Best used for protection against flying small particles

STORAGE
Can be stored in the dark and sealed condition for up to 2 years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Just air dry after the rinsing or dipping in water	100 pieces per carton
Do not wipe off the water	

Udyogi