






## IKAR HWPS RETRACTABLE BLOCK

With Plastic Housing

STANDARD : CONFORMING TO EN360:2002

INDUSTRY		IDEAL APPLICATIONS		SPECIAL FEATURES	
Construction		Working at Height		 FALL ARREST	 STRONG
Process plants		Ladder Climbing			
Grinding Unit		Loading/Unloading point			
Manufacturing Unit		Bag House and vessels maintenance			
MECHANICAL CHARACTERISTICS			PHYSICAL PARAMETERS		
Breaking Strength - 15 kN			Robust & durable casing made from high impact glass field nylon		
Breaking Force - Less than 6 kN			Has a swivel anchorage eye at one end		
			Snap hook equipped with fall indicator and swivel action		





RETRACTABLE LANYARD	AVAILABLE LENGTH
Material – Steel rope	3, 4.5, 6, 9, 12, 18, 24 mtr
Diameter - $\Phi$ 4.8 mm	STORAGE
Breaking Strength - Greater than 15 kN	Store the retractable in a dry area away from ultraviolet rays
FEATURES	Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold
Wire rope type retractable fall arrestor	CLEANING
High Impact resistance polyamide casing	Use clean piece of cloth to wipe the dust
In case a fall occurs, the automatic braking system in the block immediately arrests the fall	PACKING
Included conduit rope Maximum	1 piece per box
load capacity: 136 kg	
MARKINGS	
Manufacturers Logo, details & mailing address	
Model No., Batch No., Serial No.	
Year of Manufacturing	
Material	
Instruction Pictogram	

Udyogi