



## WL22 Safety Lanyard

STANDARD : CERTIFIED TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Construction	Work at Height
Metals & Mining	Ladder Climbing
Cement	Fall Arrest
	Rescue

### SPECIAL FEATURES



LIGHT WEIGHT



FALL RESTRAINT

### ROPE MATERIAL

44m (+/- 1mm) wide Polyester Webbing

### FEATURES

Energy Absorbing Double Polyester Webbing Lanyard

One side (Lanyard End) connected with SH-60 scaffolding hook and on other side connected with EASY 308 Carabiner

### CLEANING

Use clean piece of cloth to wipe the dust

### PACKING

10 pieces per carton



### STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

### BREAKING STRENGTH

23kN (Min)

### LANYARD LENGTH

1.8 mtrs (Hook to Hook)

### MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

### STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.