



## AGNI-UB102 FR

Safety Harness

STANDARD : CONFORMING TO EN 361:2002, IS 3521(Part 1): 2021  

INDUSTRY	IDEAL APPLICATIONS
Furnace	General Working at Height
Welding	Fall Arrest
-	Ladder Climbing

### SPECIAL FEATURES



WEBBING MATERIAL	WEBBING WIDTH
Flame Retardant Polyester tested as per ISO:15025 & ISO:9150	44 +/- 1 mm

WEBBING BREAKING STRENGTH
22kN (Min)

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High-tenacity Flame Retardant Polyester	White

METAL COMPONENTS	HARNESS COLOUR	WEIGHT
High quality alloy steel, zinc plated, free from any sharp edges	Black	900 grams

### TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 KN applied for 3 min.

### TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mtr.





#### FEATURES

- One dorsal D-ring for fall arrest
- Two textile loop sternal attachment on chest for fall arrest
- Fully adjustable chest and thigh strap
- Ideally positioned sit-strap for extended comfort
- Ideal for Welding work and flame retardant work

#### CLEANING

- Use Clean piece of cloth to wipe the dust

#### PACKING

- 10 pieces per carton

#### MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approval & IS marking
- Instruction Pictogram

#### STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct/ high heat or sunlight as this may distort the colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.